

Autolite® Spark Plug Heat Range Chart

Tabla de grados térmicos de bujías Autolite®

			A	B	C	D	E	F	G	H	I	J	
THREAD SIZE & REACH	HEX	HEAT RANGE	STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	IRIDIUM XP ENHANCED ALLOY TECHNOLOGY™	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP	
1	10mm 1/4"	HOT	3136										
		COLD											
2	10mm 1/2"	HOT	4194		5438 ⁸²⁹⁰					XST5438			
		COLD											
3	10mm 3/4"	HOT		4303						XS4303 ^{2399, 8252}			
		COLD		4302						XS4302 ^{2399, 8252}			
4	12mm 1/2"	HOT	4173										
		COLD											
4.5	12mm 3/4"	HOT		5663									
		COLD											
5	12mm 3/4"	HOT				4164				XS4164 ^{2399, 8252, 8294}			
			AR4133		AR4153	4163				XS4163 ^{2399, 8252, 8294}			
		COLD	4132 AR4132		AR4152	4162				XS4162 ^{2399, 8252, 8294}			
6	12mm 26.5mm (Gasket Seat)	HOT						APP5683	XP5684 XP5683				
		COLD							XP5682				
7	12mm 26.5mm (Gasket Seat)	HOT							XP5703 XP5702				
		COLD							XP5701				
8	12mm 26.5mm (Tapered Seat)	HOT											
		COLD						APP5465 ⁸³⁰¹					
9	14mm (Tapered Seat) .332"	HOT											
			2956 ⁸²⁹⁷							XST2956 ^{2456, 8251, 8294, 8297}			
		COLD	2954 ⁸²⁹⁷		2554 ⁸²⁹⁷					XST2554 ^{2456, 8251, 8294, 8297} XST2954 ^{2456, 8251, 8294, 8297}			
10	14mm 3/8"	HOT	458 ^{8295/258} 8293	308						XST458 ^{2456, 8251, 8294} XST258 ^{2456, 8251, 8293, 8294}	2247		
				306							2246 ²³⁹⁹		
			295/456 ⁸²⁹⁵			847	AP847 ⁸²⁹¹	APP847 ⁸²⁹¹			2245 ^{2399, 9532}		
			255 ⁸²⁹³			86	AP86				XST255 ^{8251, 8293, 8294}	2244 ²³⁹⁹	
					4275 75	85	AP85				XS85 ^{2399, 8252, 8294}	2243 ^{2399, 9532}	
				303	2976 ⁸²⁹³		AP303				XST2976 ^{8251, 8293, 8294}		
			254 ⁸²⁹³								XST254 ^{8251, 8293, 8294}		
11	14mm 7/16"	HOT			437								
			216/4316								2327 ²³⁹⁹		
		COLD									2325 ²³⁹⁹		

Utilize el índice para ver notas a pie.

²³⁹⁹ Resistor ²⁴⁵⁶ Non-resistor ⁸²⁵¹ Xtreme Start™ ⁸²⁵² Xtreme Sport® ⁸²⁹⁰ Tapered seat ⁸²⁹¹ .060" Gap ⁸²⁹³ Bantam plug with 3/4" hex ⁸²⁹⁴ Power tip
⁸²⁹⁵ Special lawnmower plug ⁸²⁹⁷ Bantam plug ⁸³⁰¹ Special power tip ⁹⁵³² Military waterproof

Autolite® Spark Plug Heat Range Chart

Tabla de grados térmicos de bujías Autolite®

			A	B	C	D	E	F	G	H	I	J		
THREAD SIZE & REACH	HEX	HEAT RANGE	STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	IRIDIUM XP ENHANCED ALLOY TECHNOLOGY™	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP		
12	14mm 1/2"	13/16"	HOT								2407 ^{2399, 9532, 8294}			
				2656	425/2665 ⁹⁵²⁶	275		AP425 ⁸²⁹⁸			XS2666	2285		
						4114							2344 ^{2399, 9532} 2384 ^{2399, 9532}	
				414										
				4093	422 ⁹⁵²⁶		4123/4122 ⁹⁵²⁶					XS4093 ⁸²⁵²		2852 ²⁴⁵⁶
				4092	421 ⁹⁵²⁶		4121 ⁹⁵²⁶					XS4092 ⁸²⁵²		2872 ^{2456, 8300}
		COLD	411, 2634 ⁸²⁹⁶	2645 ⁹⁵²⁶					XS2644		2892 ^{2456, 8292}			
13	14mm 3/4"	5/8"	HOT				3926		APP3926	XP3926	XST3926 ^{2399, 8251, 8294}			
							985 ⁸³⁰¹	AP985 ⁸³⁰¹	APP985 ⁸³⁰¹	XP985 ⁸³⁰¹	XS985 ^{2399, 8252, 8301}			
						3924/5184 ⁸²⁹¹ /5224 ⁸³⁰²		AP3924/ AP5184 ⁸²⁹¹ AP5405 ⁸³⁰⁸ / AP5224 ⁸³⁰²	APP3924/ APP5224 ⁸³⁰²	XP3924/ XP5405 ⁸³⁰⁸ / XP5224 ⁸³⁰²	XST3924 ^{2399, 8251} XS3924 ^{2399, 8252} XS5224 ^{2399, 8252, 8302}			
						3923/5503 ⁸³⁰⁸		AP3923/ AP5503 ⁸³⁰⁸	APP3923/ APP5503 ⁸³⁰⁸	XP3923/ XP5503 ⁸³⁰⁸	XS3923 ^{2399, 8252}			
					COLD	AR3935		3922			XP3922	XS3922 ^{2399, 8252}		
14	14mm 3/4"	13/16"	HOT				4345 ⁸³⁰³							
							66/646 ⁸²⁹¹	AP66/ AP646 ⁸²⁹¹	APP66/ APP646 ⁸²⁹¹	XP646 ⁸²⁹¹				
					405		65/925 ⁸³⁰³ / 4265	AP65	APP65		XST4265 ^{2399, 8251, 8294} XS65 ^{2399, 8252, 8294}			
				4056	404		64/2744 ⁸³⁰²	AP64/ AP2744 ⁸³⁰² / AP404 ⁸²⁹⁸	APP64	XP64		2304 ^{2399, 9532}		
							63/4263	AP63	APP63	XP63	XS63 ^{2399, 8252, 8294}			
				4055	403			AP403			XST4055 ^{2456, 8251}			
					402	4252 AR52	62	AP62			XS62 ^{2399, 8252, 8294}			
					2526 ⁸³⁰⁴ / 2626 ⁸³⁰⁴	4251 AR51	60				XS61 ^{2399, 8252, 8294}			
				4054		AR50					XS4064 ^{2399, 8252, 8294}			
					4063 ¹⁰¹⁴³ / 4063S ¹⁰¹⁴⁴						XS4063 ^{2399, 8252, 8294}			
	4062 ¹⁰¹⁴³ / 4062S ¹⁰¹⁴⁴ / 4062S-5 ¹⁰¹⁴⁴						XS4062 ^{2399, 8252, 8294}							
	COLD	4051	4061											
15	14mm (Tapered Seat) .460"	5/8"	HOT		147/687 ⁸²⁹¹									
							26/666 ⁸²⁹¹	AP26/ AP666 ⁸²⁹¹	APP26/ APP666 ⁸²⁹¹	XP26/ XP666 ⁸²⁹¹				
					145/685 ⁸²⁹¹		25/5285 ⁸³⁰⁶ 665	AP25/ AP145 ⁸²⁹⁸	APP25/ APP145 ⁸²⁹⁸	XP25				
					144		664 24	AP24	APP24	XP24				
	COLD				23	AP23	APP23							

Utilize el índice para ver notas a pie.

²³⁹⁹ Resistor ²⁴⁵⁶ Non-resistor ⁸²⁵¹ Xtreme Start™ ⁸²⁵² Xtreme Sport® ⁸²⁹¹ .060" Gap ⁸²⁹² Series air gap ⁸²⁹⁴ Power tip ⁸²⁹⁶ .040" Gap ⁸²⁹⁸ Standard tip ⁸³⁰⁰ Large gap
⁸³⁰¹ Special power tip ⁸³⁰² Special tip design ⁸³⁰³ Long electrodes ⁸³⁰⁴ Special plug for MAZDA rotary engine only ⁸³⁰⁶ Special tip design for Ford
⁸³⁰⁸ Longer upper end insulator ⁹⁵²⁶ Inductive suppressor ⁹⁵³² Military waterproof ¹⁰¹⁴² Loose terminal nut ¹⁰¹⁴⁴ Solid terminal nut

Autolite® Spark Plug Heat Range Chart

Tabla de grados térmicos de bujías Autolite®

			A	B	C	D	E	F	G	H	I	J
THREAD SIZE & REACH	HEX	HEAT RANGE	STANDARD (NON-RESISTOR)	STANDARD (RESISTOR)	POWER TIP (NON-RESISTOR)	POWER TIP (RESISTOR)	PLATINUM	DOUBLE PLATINUM	IRIDIUM XP ENHANCED ALLOY TECHNOLOGY™	PREMIUM SMALL ENGINE	SHIELDED (RESISTOR)	SURFACE GAP
16 14mm (Tapered Seat) .708" Full Thread	5/8"	HOT				606 ⁸²⁹¹ /106	AP606 ⁸²⁹¹ / AP106	APP606 ⁸²⁹¹ / APP106	XP606 ⁸²⁹¹ / XP106			
						605 ⁸²⁹¹ / 5245 ⁸³⁰²	AP605 ⁸²⁹¹ / AP105/ AP5145 ⁸³⁰⁷ / AP5245 ⁸³⁰²	APP605 ⁸²⁹¹ / APP105/ APP5145 ⁸³⁰⁷ / APP5245 ⁸³⁰²	XP605 ⁸²⁹¹ / XP105/ XP5245 ⁸³⁰²			
						104/5144 ⁸³⁰⁷	AP104/ AP5144 ⁸³⁰⁷	APP104/ APP5144 ⁸³⁰⁷	XP104			
		COLD				103/5143 ⁸³⁰⁷ / 5243 ⁸³⁰²	AP103/ AP5143 ⁸³⁰⁷ / AP5243 ⁸³⁰²	APP103/ APP5243 ⁸³⁰²	XP103/ XP5143 ⁸³⁰⁷ / XP5243 ⁸³⁰²			
17 14mm (Tapered Seat) .708" Half Thread	5/8"	HOT				2546 ⁸³⁰⁶ /766	AP2546/AP766	APP2546				
						2545 ⁸³⁰⁶ /765	AP2545/AP765	APP2545/ APP765	XP5145 ⁸³⁰⁵			
						2544 ⁸³⁰⁶ /764	AP2544/AP764	APP2544/ APP764	XP5144 ⁸³⁰⁵			
		COLD				2543	AP2543					
17.5 14mm (Tapered Seat) .982"	5/8"	HOT							XP6043 ¹⁰¹⁵²			
		COLD										
18 14mm (Tapered Seat) 1"	5/8"	HOT					AP5426 ⁸³⁰²	APP5426 ⁸³⁰²	XP5426 ⁸³⁰²			
		COLD					AP5263 ^{8305, 8307}	APP5263 ^{8305, 8307}	XP5263 ^{8305, 8307} / XP5363 ⁸³⁰⁵			
19 14mm (Gasket Seat) 1"	5/8"	HOT										
		COLD				6003 ⁸³⁰⁷		APP5325	XP5325/ XP6003 ⁸³⁰⁷			
20 16mm (Tapered Seat) High Thread 1"	9/16"	HOT					HT2					
							HT15					
								HT1				
		COLD						HT0				
21 18mm .445"	1"	HOT										
		COLD	2695									
22 18mm 1/2"	7/8"	HOT		388							2227 ²³⁹⁹	
					3116						2226 ^{2399, 9532}	
				386							2225 ²³⁹⁹	
											2224	
		COLD	373								2223 ^{2399, 9532}	
23 18mm (Tapered Seat) .460"	13/16"	HOT	35			46	AP46	APP46				
						45/5125 ⁸³⁰⁷	AP45/ AP5125 ⁸³⁰⁷	APP45/ APP5125 ⁸³⁰⁷				
		COLD		124			AP124					
24 18mm .968"	13/16"	HOT		824 ⁸²⁹⁶								
		COLD										
25 18 5/8"	7/8" - 15/16"	HOT	3077									
		COLD	3076									
26 1/2" Pipe Thread	7/8"	HOT	3095									
		COLD										

Utilize el índice para ver notas a pie.

²³⁹⁹ Resistor ⁸²⁹¹ .060" Gap ⁸²⁹⁶ .040" Gap ⁸³⁰² Special tip design ⁸³⁰⁵ Full thread ⁸³⁰⁶ Special tip design for Ford ⁸³⁰⁷ Long shell design ⁹⁵³² Military waterproof

¹⁰¹⁵² Long projection